Targeted Application to Reduce Pesticide Rates


Ken Giles
David Slaughter

Biological & Agricultural Engineering Department University of California, Davis USA

California Department of Pesticide Regulation VOC Symposium

Sacramento, CA 23 May 2007





Three critical aspects of ag spraying

Successful changes in practices address all three



Agrochemical application in California

Proximity to sensitive areas, either natural or man-made is common.



Tools to reduce application rates:

- \Rightarrow Improved nozzles
 - * Droplet size management
 - * Better targeting



- \Rightarrow Adjuvants
 - * Reduce liquid rates
 - * Achieve small droplet quality deposition and efficacy with larger droplets





- \Rightarrow Targeted application
 - * Sensors and controllers
 - * Reduce non-target deposition




Nozzle Technology

- Trend toward larger droplets
- Using air induction
- Manipulating droplet velocities



Air induction nozzle


- A passive air flow
- Reduces small droplets
- Can create bubbles in droplets



Air induction nozzle


water






Air induction nozzle


water + 0.5% surfactant




Droplet deposition




Water
0.508 mm orifice
5 cm distance
70 kPa
100 ms pulse





Poor spread

Water + surfactant
0.508 mm orifice
5 cm distance
70 kPa
100 ms pulse






Splash

Water + surfactant + polymer

0.508 mm orifice5 cm distance70 kPa100 ms pulse





Good spread

Splash inhibited



Effect of adjuvant on deposition



Silicone surfactant 50 gallons / acre

No adjuvant 100 gal / acre





Air blast sprayer AI nozzles @ 160 gals/ac W/ alternate adjuvant



Miller et al. (2003) concluded: "Most of the spray movement out of the tree canopy was in the spaces between trees..."

"One way to reduce drift may be to turn off the spray between tree crowns...



Spray deposit partitioning in orchards

<u>Author</u>	Condition	Ground	<u>Target</u>	<u>Drift</u>
Seiber	Dormant	25 – 45%	-	-
Cross	Both	43 - 63%	-	16%
Vercruysse	Both	-	56 – 68%	-
Pergher	In season	-	37 – 62%	_
Fox	"Sparse"	57%	-	-
Miller	In season	22%	57%	4.6 (16%)

Ultrasonic measurement of trees for control of spray sections.



Savings depends on orchard age, size, gaps, etc.

Some trials have shown 50 - 70 % savings.

Field test – dormant plums Chico




Air-O-Fan 2D40 engine-driven sprayer "Smart Spray" ultrasonic control system (retrofit)

Field test – dormant walnuts Davis



Nozzle configuration was "center-weighted" spray





Field test – dormant almonds Ceres

Durand-Wayland AF500 Smart Sprayer




Nozzle configuration was "center-weighted" spray

0.5 kg/ha Lorsban (chlopyrifos)



Deposition sampling - almonds



Performance results

3 crops, 3 chemicals, 3 sprayers, 3 locations, 3 operators ...

Use of system had no significant effect on target deposition

- Plum orchard
 - 15% reduction in a.i. rate
 - 5% less ground deposit
- Walnut orchard
 - 45% reduction in a.i. rate
 - 58% less ground deposit
- Almond orchard -
 - 22% reduction in a.i. rate
 - 71% less ground deposit

Based on these results, a run-off experiment was conducted in a 40 acre prune orchard in Biggs.



Field test – Prunes Biggs



Durand-Wayland AF500 Smart Sprayer

Measurements:


Spray savings Ground deposit Runoff




Results from "Smart" Spraying Spray Savings: 39% Ground Deposit: - 54% Diazinon in Runoff: - 44%




A typical target scene within the row



A typical target scene within the row




Process for image analysis








Replacing chemical selectivity with spatial selectivity






The concept..

"Leaf-specific" agriculture

Process for spatially selective application of nonselective herbicide



Micro boom and micro boom sections of micro nozzles



One micro boom section per cell

Fast valves for flow control

Micro-nozzles for dosing

Target plants







